Amendments to the Claims:

1

2	This listing of claims will replace all prior versions, and listings of claims in the application:
3	Listing of Claims:
1	1 (currently amended): A device for applying a magnetic field to a microtiter
2	plate, said device comprising:
3	a substrate; and
4	a plurality of magnetic elements disposed on said substrate, wherein said plurality
5	of magnetic elements are arranged parallel to each other such that the centerline longitudinal axis
6	of each magnetic element is approximately centered directly under an entire a row or column of
7	wells of a microtiter plate when said microtiter plate is positioned upon the device.
1	2 (original): The device of claim 1, wherein said substrate is comprised of a
2	material selected from the group consisting of polymers, plastics, pyrex, quartz, resins, silicon,
3	silica, silica-based materials, carbon, metals, inorganic glass and combinations thereof.
1	3 (original): The device of claim 1, wherein said substrate is comprised of a
2	material selected from the group consisting of organic, inorganic, biological, nonbiological
3	materials and combinations thereof.
1	4 (original): The device of claim 1, wherein said substrate is substantially disc-
2	shaped, square-shaped, rectangle-shaped or combinations thereof.
1	5 (original): The device of claim 1, wherein said substrate has substantially the
2	same shape and size as said microtiter plate.
1	6 (original): The device of claim 1, wherein the device comprises one magnetic
2	element for each column of wells of the microtiter plate.

Appl. No. 09/992,534 Amdt. dated September 3, 2004 Reply to Office Action of March 4, 2004

l	7 (original): The device of claim 1, wherein the device comprises twenty-lour
2	magnetic elements and the longitudinal axis of each element is approximately centered under a
3	column of wells of a 384-well microtiter plate.
1	8 (original): The device of claim 6, wherein each magnetic element is
2	approximately the same length of a column of wells of the microtiter plate.
1	9 (original): The device of claim 1, wherein the device comprises one magnetic
2	element for each row of wells of the microtiter plate.
1	10 (original): The device of claim 9, wherein the device comprises sixteen
2	magnetic elements and the longitudinal axis of each element is approximately centered under a
3	row of wells of a 384-well microtiter plate.
1	11 (original): The device of claim 9, wherein each magnetic element is
2	approximately the same length of a row of wells of the microtiter plate.
1	12 (original): The device of claim 1, wherein adjacent magnetic elements are in
2	contact with each other.
1	13 (original): The device of claim 1, wherein adjacent magnetic elements are
2	separated from on another by a non-magnetic material.
1	14 (original): The device of claim 1, wherein each magnetic element is
2	approximately as wide as the diameter of a well of the microtiter plate.
1	15 (original): The device of claim 1, wherein the device does not include a
2	mechanism for horizontal circular translation of the microtiter plate.
1	16 (original): The device of claim 1, wherein the device further comprises a
2	microtiter plate positioned upon the magnetic elements.

Appl. No. 09/992,534 Amdt. dated September 3, 2004 Reply to Office Action of March 4, 2004

1	17 (original): The device of claim 16, wherein one or more wells of the
2	microtiter plate contains a suspension of magnetic particles.
1	18 (original): The device of claim 17, wherein the suspension comprises
1	
2	immunoassay reagents.
1	19 (original): The device of claim 17, wherein the suspension comprises a
2	primer extension reaction.
1	20 (original): The device of claim 19, wherein the primer extension reaction is a
2	DNA sequencing reaction.
1	21 (original): The device of claim 19, wherein the suspension comprises dye-
2	labeled molecules and a polymer into which dye-labeled molecules are incorporated, and
3	particles that comprise a paramagnetic moiety and a porous hydrophobic material entrapped
4	within a hydrophilic matrix.
	22-25 (canceled)
1	26 (new): The device of claim 1, wherein each of said magnetic elements is
2	configured to form a magnetic field having a strength greater than approximately twelve Kgauss.